

Material		Properties
PTEFE COATED GLASS FIBRE 'FRYING SHEETS' STANDARD COLOURS BROWN & BLACK (FG)		Directives: EU1935/2004, 2007/19EC, 2023/2006, 2008/39/EC, 89/109/EEC, 78/142/EEC, 82/711/EEC, 85/572/EEC, 90/128/EEC, 92/39/EEC, 93/8/EEC, 93/9/EEC, 93/10/EEC
Technical data		Applications
General Properties		The material is according to Reach and RoHS This product, when used as the food contact surface of equipment in the preparation of food are in compliance with the Federal Food, Drug and Cosmetic Act, and the applicable Food Additive Regulations, including 21CFR, Section 177.1550
Weight	220 g/m ² +/-5%	
Thickness	112µm	
PTFE percentage	48% +/-2%	
Fabric & Coating		
Fabric material	Glass	
Coating	PTFE	
Mechanical Properties		
Tensile Strength*	1000 N/5cm	
Tear Strength**	20N	
Dielectric Breakdown (V)***	N/A	
Max. cont. Temperature (PTFE)	240°C	
Min. Temperature	-73°C	
Disclaimer		Availability
<p>The information given and, in particular, any parameters, should be used for guidance purpose only. The Company does not give any warranty that the product will be suitable for the use intended by the Costumer. We reserve the right to make alternations of the data and the properties of the material without notice</p>		<p>1000 & 1230mm standard widths Made to Custom size</p>

Rev.: 2014-01-31/151PH

*BS 3424 Part 4 Method 6

** BS 7304 Part 4

*** BS 2782 Part 2 Method 220