

SCAN-TEF 01-07X

DATASHEET

		DATASHEET
Material		Properties
PTEFE COATED GLASS FIBRE		Directives: EF1935/2004, 2002/7/EC, 2007/19EC, 2008/39/EC
Technical data		Applications
General Properties		The material is according to Reach and RoHS
Weight	146 g/m² +/-5%	This product, when used as the food contact surface of equipment in the preparation of food are in compliance with the Federal Food, Drug and Cosmetic Act, and the applicable Food Additive Regulations, including 21CFR, Section 177.1550
Thickness	74μm	
PTFE percentage	66% +/-2%	
Fabric & Coating		
Fabric material	Glass	
Coating	PTFE	
Mechanical Properties		
Tensile Strength*	500 N/5cm	
Tear Strength**	10N	
Dielectric Breakdown***	2000V	
Max. cont. Temperature	260°C	
Min. Temperature	-170°C	
Disclaimer		Availability
The information given and, in particular, any parameters, should be used for guidance purpose only. The Company does not give any warranty that the product will be suitable for the use intended by the Costumer. We reserve the right to make alternations of the data and the properties of the material without notice		1000mm standard width

Rev.: 2010-07-06/39(3)PH

*BS 3424 Part 4 Method 6

** BS 7304 Part 4

*** BS 2782 Part 2 Method 220