

Material		Properties
PTEFE COATED GLASS FABRIC SELF-ADHESIVE WITH BACKING PAPER AND ACRYLIC ADHESIVE		Directives: EU1935/2004, 2002/7/EC, 2007/19EC, 2008/39/EC
Technical data		Applications
General Properties		The material is according to Reach and RoHS This product, when used as the food contact surface of equipment in the preparation of food are in compliance with the Federal Food, Drug and Cosmetic Act, and the applicable Food Additive Regulations, including 21CFR, Section 177.1550
Weight Before Adhesive	220 g/m ² +/-5%	
Thickness Before adhesive	130µm	
PTFE percentage	60% +/-2%	
Adhesive Thickness	50 µm	
Fabric & Coating		
Fabric material	Glass	
Coating	PTFE	
Adhesive (PSA)	Silicone	
Mechanical Properties		
Breaking Strength*	1200 N/5cm	
Max. cont. Temperature (PTFE)	170°C	
Min. Temperature	-40°C	
Disclaimer		Availability
<p>The information given and, in particular, any parameters, should be used for guidance purpose only. The Company does not give any warranty that the product will be suitable for the use intended by the Costumer. We reserve the right to make alternations of the data and the properties of the material without notice</p>		1000mm standard width

Rev.: 2014-03-24/50(5V)BB

*BS 3424 Part 4 Method 6

** BS 7304 Part 4

*** BS 2782 Part 2 Method 220