

Material		Properties
PTEFE COATED GLASS FABRIC SELF-ADHESIVE WITH BACKING PAPER AND SILICONE ADHESIVE		Directives: EU1935/2004, 2002/7/EC, 2007/19EC, 2008/39/EC
Technical data		Applications
<b>General Properties</b>		The material is according to Reach and RoHS  This product, when used as the food contact surface of equipment in the preparation of food are in compliance with the Federal Food, Drug and Cosmetic Act, and the applicable Food Additive Regulations, including 21CFR, Section 177.1550
Weight before Adhesive	309 g/m <sup>2</sup> +/-5%	
Thickness before adhesive	142µm	
PTFE percentage	65% +/-2%	
Adhesive Thickness	60 µm	
<b>Fabric &amp; Coating</b>		
Fabric material	Glass	
Coating	PTFE	
Adhesive (PSA)	Silicone	
<b>Mechanical Properties</b>		
Tensile Strength*	900 N/5cm	
Tear Strength**	10N	
Dielectric Breakdown***	3000V	
Max. cont. Temperature (PTFE)	260°C	
Max. cont. Temperature (adhesive)	180°C	
Min. Temperature	-73°C	
Disclaimer		Availability
<p>The information given and, in particular, any parameters, should be used for guidance purpose only. The Company does not give any warranty that the product will be suitable for the use intended by the Costumer. We reserve the right to make alternations of the data and the properties of the material without notice</p>		1000mm standard width

Rev.: 2014-02-20/A69(01)BB

\*BS 3424 Part 4 Method 6

\*\* BS 7304 Part 4

\*\*\* BS 2782 Part 2 Method 220